

# Classic's Comparison Chart



	Classic			Classic SL			Classic SLE
Modelo	150	200	250	150	200	250	150
Intensidad máxima	96	79	61	96	79	61	96
Voltaje máximo	150	200	250	150	200	250	150
HyperVOC Extended VOC Limit <sup>1</sup>	●	●	●	●	●	●	●
Voltaje máximo batería	72	72	72	72	72	72	72
Solar	●	●	●	●	●	●	●
Wind	●	●	●				
Hidro	●	●	●				
Internet and Ethernet Ready (Mod Bus)	●	●	●				●
Detección fallo tierra	●	●	●	●	●	●	●
Detección fallo por arco	●	●	●				
Display gráfico	●	●	●	●	●	●	●
Firmware actualizable por usuario	●	●	●	●	●	●	
MNGP Multiple Display Support <sup>2</sup>	●	●	●	●	●	●	●
Salida auxiliar	2	2	2	2	2	2	2
Software para PC e Internet gratuitos	●	●	●				●
380 Days Data Logging <sup>3</sup>	●	●	●	●	●	●	●
Baterías soportadas (Abiertas, AGM, Gel)	●	●	●	●	●	●	●
Garantía 5 años	●	●	●	●	●	●	●
Sustancialmente fabricado en EEUU.	●	●	●	●	●	●	●